

Table 2 .30-30 Factory Load Test
 Thompson-Center Contender
 14" Barrel

Load	150-gr Bullets				170-gr Bullets			
	Velocity	Std D	Grp 4	Grp 3/4	Velocity	Std D	Grp 4	Grp 3/4
1 Win Power Point	2003	100.0	3.26	2.35	1938	40.4	3.56	1.99
			2.63	1.78			1.32	1.05
2 Win Silver Tip	2133	7.7	4.18	1.38	1939	10.6	1.89	0.77
			3.04	1.64			2.13	1.30
3 Rem Cor-Lokt	2161	11.9	2.38	1.72	1998	6.5	2.85	2.11
			1.96	1.40			2.93	2.66
4 Hornady Custom	2166	10.3	1.76	0.46	2021	6.3	2.81	1.23
			1.91	1.23			2.67	1.77
5 Federal Classic	2176	44.9	3.96	1.96	1983	10.4	3.30	1.76
			3.25	2.96			2.54	1.54
6 Speer Nitrex	2102	14.7	3.36	1.61	NA	----	-----	-----
			2.17	1.26			-----	-----
Average All Loads	2124		2.82	1.64	1976		2.6	1.62
			SD 0.81	SD 0.62			SD 0.63	SD 0.53

- Velocity In feet-per-second, measured at 15 feet. Each is the average of eight rounds.
 (Pact Model 2 Chronograph - Sky screens at 24")
- Std D The standard deviation of the eight measured rounds.
- Grp 4 Center-to-center measurement in MOA of a 4-shot group. Two groups for each load.
- Grp 3/4 Center-to-center measurement of the best 3 shots in each 4-shot group.